

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1028_ACTV_DIAG_PVD_PAD

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Active Diagnoses - PVD or PAD	Asmt		Code	1	1553-1553

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
0		Not checked (No)
1		Checked (Yes)
-		Not assessed (no information)

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-5670	Consistency	Fatal	(a) If M1028_ACTV_DIAG_NOA = [0], then at least one of M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [1]. (b) If M1028_ACTV_DIAG_NOA = [1], then M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [0]. (c) If M1028_ACTV_DIAG_NOA = [-], then at least one of M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [-] and the other item must equal [0,-].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1028_ACTV_DIAG_DM

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Active Diagnoses - Diabetes Mellitus	Asmt		Code	1	1554-1554

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
0		Not checked (No)
1		Checked (Yes)
-		Not assessed (no information)

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-5670	Consistency	Fatal	(a) If M1028_ACTV_DIAG_NOA = [0], then at least one of M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [1]. (b) If M1028_ACTV_DIAG_NOA = [1], then M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [0]. (c) If M1028_ACTV_DIAG_NOA = [-], then at least one of M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [-] and the other item must equal [0,-].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1028_ACTV_DIAG_NOA

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Active Diagnoses - None of the above	Asmt		Code	1	1627-1627

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
0		Not checked (No)
1		Checked (Yes)
-		Not assessed (no information)

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-5670	Consistency	Fatal	(a) If M1028_ACTV_DIAG_NOA = [0], then at least one of M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [1]. (b) If M1028_ACTV_DIAG_NOA = [1], then M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [0]. (c) If M1028_ACTV_DIAG_NOA = [-], then at least one of M1028_ACTV_DIAG_PVD_PAD and M1028_ACTV_DIAG_DM must equal [-] and the other item must equal [0,-].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1021_PRIMARY_DIAG_ICD

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Primary diagnosis ICD code	Asmt		ICD	8	1359-1366

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
ICD-10		ICD-10 diagnosis code

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-4885	Format	Fatal	FORMATTING OF ICD-10 DIAGNOSIS CODES ICD-10 diagnosis codes must conform with the following formatting rules: a) Character 1 must be alphabetic [A-Z,a-z]. b) Character 2 must be numeric [0-9]. c) Character 3 must be numeric [0-9] or alphabetic [A-Z,a-z]. d) Character 4 must be a decimal point. e) Characters 5 through 8 must be numeric [0-9], alphabetic [A-Z,a-z], or caret [^]. f) If any character 5 through 8 is equal to [^], all subsequent characters must equal [^]. Note that additional formatting rules for particular items may further restrict the range of allowable values in character 1. Also note that an entirely blank ICD code must be submitted as a single caret: [^].
-4900	Format	Fatal	RESTRICTIONS ON ICD-10 DIAGNOSIS CODES Character 1 of the ICD code must not equal [V,W,X,Y,v,w,x,y].
-5001	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if a value submitted in items M1021_PRIMARY_DIAG_ICD, M1023_OTH_DIAG1_ICD, M1023_OTH_DIAG2_ICD, M1023_OTH_DIAG3_ICD, M1023_OTH_DIAG4_ICD, or M1023_OTH_DIAG5_ICD is not equal to [^], it must not equal (must not duplicate) any value submitted in the remaining items in this list.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].
-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON =[01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Supplemental Information

Info ID	Type	Text
-9110	Information	<p>If state law prohibits transmission of certain ICD codes (e.g., HIV or STD diagnoses), these codes will be removed by iQIES if found on records submitted by HHAs within that state. If any item within an ICD list contains such a code on a submitted record, it will be removed from the list. If any of these items is removed, but a valid code remains in a subsequent item on the list, the subsequent codes will be "moved up" so that no missing codes remain.</p> <p>Therefore, if a non-blank value is required in an ICD code list and all of the submitted items in that list contain blank and/or prohibited codes, a fatal error will result and the record will be rejected. As long as at least one item in such a list contains a non-blank, correctly-formatted, allowable code, a fatal error will not occur.</p>
-9150	Information	<p>If an ICD list contains multiple codes, there should be no intervening items in the list which are equal to [^]. For example, if a 5-item list is populated with 3 ICD codes, those codes should occupy items 1, 2, and 3; items 4 and 5 should be equal to [^].</p> <p>If the system finds a list which contains intervening items which are equal to [^], the values that are later in the list will be moved up to eliminate the intervening blank [^] item values. Diagnoses are only moved up within the same type of</p>
-9170	Information	<p>SUBMITTING ICD-10 DIAGNOSIS CODES</p> <p>If the ICD-10 item is active, it must be submitted as an 8 character, fixed-format string with all blanks replaced with [^], and with a decimal point as the 4th character. The only exception to this rule is that an entirely blank ICD-10 item must be submitted as a single [^].</p> <p>For example:</p> <ul style="list-style-type: none">-The ICD-10 code "A12." would be submitted as [A12.^^^].-The ICD-10 code "A12.3" would be submitted as [A12.3^^].-The ICD-10 code "A12.34" would be submitted as [A12.34^^].-The ICD-10 code "A12.345" would be submitted as [A12.345^]-The ICD-10 code "A12.3456" would be submitted as [A12.3456]-An entirely blank ICD-10 code would be submitted as [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1021_PRIMARY_DIAG_SEVERITY

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Primary diagnosis severity rating	Asmt		Code	2	1367-1368

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
00		Asymptomatic, no treatment needed at this time
01		Symptoms well controlled with current therapy
02		Symptoms controlled with difficulty, affecting daily functioning; patient needs ongoing monitoring
03		Symptoms poorly controlled: patient needs frequent adjustment in treatment and dose monitoring
04		Symptoms poorly controlled: history of re-hospitalizations
^		No severity rating

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-4991	Consistency	Warning	If M0100_ASSMT_REASON=[01,03], then M1021_PRIMARY_DIAG_SEVERITY should equal [01,02,03,04,^].
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].
-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON = [01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG1_ICD

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 1: ICD code	Asmt		ICD	8	1369-1376

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
ICD-10		ICD-10 diagnosis code
^		Blank (no diagnosis code)

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-4885	Format	Fatal	FORMATTING OF ICD-10 DIAGNOSIS CODES ICD-10 diagnosis codes must conform with the following formatting rules: a) Character 1 must be alphabetic [A-Z,a-z]. b) Character 2 must be numeric [0-9]. c) Character 3 must be numeric [0-9] or alphabetic [A-Z,a-z]. d) Character 4 must be a decimal point. e) Characters 5 through 8 must be numeric [0-9], alphabetic [A-Z,a-z], or caret [^]. f) If any character 5 through 8 is equal to [^], all subsequent characters must equal [^]. Note that additional formatting rules for particular items may further restrict the range of allowable values in character 1. Also note that an entirely blank ICD code must be submitted as a single caret: [^].
-5001	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if a value submitted in items M1021_PRIMARY_DIAG_ICD, M1023_OTH_DIAG1_ICD, M1023_OTH_DIAG2_ICD, M1023_OTH_DIAG3_ICD, M1023_OTH_DIAG4_ICD, or M1023_OTH_DIAG5_ICD is not equal to [^], it must not equal (must not duplicate) any value submitted in the remaining items in this list.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON = [01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Supplemental Information

Info ID	Type	Text
-9110	Information	<p>If state law prohibits transmission of certain ICD codes (e.g., HIV or STD diagnoses), these codes will be removed by iQIES if found on records submitted by HHAs within that state. If any item within an ICD list contains such a code on a submitted record, it will be removed from the list. If any of these items is removed, but a valid code remains in a subsequent item on the list, the subsequent codes will be "moved up" so that no missing codes remain.</p> <p>Therefore, if a non-blank value is required in an ICD code list and all of the submitted items in that list contain blank and/or prohibited codes, a fatal error will result and the record will be rejected. As long as at least one item in such a list contains a non-blank, correctly-formatted, allowable code, a fatal error will not occur.</p>
-9150	Information	<p>If an ICD list contains multiple codes, there should be no intervening items in the list which are equal to [^]. For example, if a 5-item list is populated with 3 ICD codes, those codes should occupy items 1, 2, and 3; items 4 and 5 should be equal to [^].</p> <p>If the system finds a list which contains intervening items which are equal to [^], the values that are later in the list will be moved up to eliminate the intervening blank [^] item values. Diagnoses are only moved up within the same type of</p>
-9170	Information	<p>SUBMITTING ICD-10 DIAGNOSIS CODES</p> <p>If the ICD-10 item is active, it must be submitted as an 8 character, fixed-format string with all blanks replaced with [^], and with a decimal point as the 4th character. The only exception to this rule is that an entirely blank ICD-10 item must be submitted as a single [^].</p> <p>For example:</p> <ul style="list-style-type: none">-The ICD-10 code "A12." would be submitted as [A12.^^^].-The ICD-10 code "A12.3" would be submitted as [A12.3^^].-The ICD-10 code "A12.34" would be submitted as [A12.34^^].-The ICD-10 code "A12.345" would be submitted as [A12.345^]-The ICD-10 code "A12.3456" would be submitted as [A12.3456]-An entirely blank ICD-10 code would be submitted as [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG1_SEVERITY

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 1: severity rating	Asmt		Code	2	1377-1378

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
00		Asymptomatic, no treatment needed at this time
01		Symptoms well controlled with current therapy
02		Symptoms controlled with difficulty, affecting daily functioning; patient needs ongoing monitoring
03		Symptoms poorly controlled: patient needs frequent adjustment in treatment and dose monitoring
04		Symptoms poorly controlled: history of re-hospitalizations
^		No severity rating

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].
-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON =[01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG2_ICD

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 2: ICD code	Asmt		ICD	8	1379-1386

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
ICD-10		ICD-10 diagnosis code
^		Blank (no diagnosis code)

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-4885	Format	Fatal	FORMATTING OF ICD-10 DIAGNOSIS CODES ICD-10 diagnosis codes must conform with the following formatting rules: a) Character 1 must be alphabetic [A-Z,a-z]. b) Character 2 must be numeric [0-9]. c) Character 3 must be numeric [0-9] or alphabetic [A-Z,a-z]. d) Character 4 must be a decimal point. e) Characters 5 through 8 must be numeric [0-9], alphabetic [A-Z,a-z], or caret [^]. f) If any character 5 through 8 is equal to [^], all subsequent characters must equal [^]. Note that additional formatting rules for particular items may further restrict the range of allowable values in character 1. Also note that an entirely blank ICD code must be submitted as a single caret: [^].
-5001	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if a value submitted in items M1021_PRIMARY_DIAG_ICD, M1023_OTH_DIAG1_ICD, M1023_OTH_DIAG2_ICD, M1023_OTH_DIAG3_ICD, M1023_OTH_DIAG4_ICD, or M1023_OTH_DIAG5_ICD is not equal to [^], it must not equal (must not duplicate) any value submitted in the remaining items in this list.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON = [01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Supplemental Information

Info ID	Type	Text
-9110	Information	<p>If state law prohibits transmission of certain ICD codes (e.g., HIV or STD diagnoses), these codes will be removed by iQIES if found on records submitted by HHAs within that state. If any item within an ICD list contains such a code on a submitted record, it will be removed from the list. If any of these items is removed, but a valid code remains in a subsequent item on the list, the subsequent codes will be "moved up" so that no missing codes remain.</p> <p>Therefore, if a non-blank value is required in an ICD code list and all of the submitted items in that list contain blank and/or prohibited codes, a fatal error will result and the record will be rejected. As long as at least one item in such a list contains a non-blank, correctly-formatted, allowable code, a fatal error will not occur.</p>
-9150	Information	<p>If an ICD list contains multiple codes, there should be no intervening items in the list which are equal to [^]. For example, if a 5-item list is populated with 3 ICD codes, those codes should occupy items 1, 2, and 3; items 4 and 5 should be equal to [^].</p> <p>If the system finds a list which contains intervening items which are equal to [^], the values that are later in the list will be moved up to eliminate the intervening blank [^] item values. Diagnoses are only moved up within the same type of</p>
-9170	Information	<p>SUBMITTING ICD-10 DIAGNOSIS CODES</p> <p>If the ICD-10 item is active, it must be submitted as an 8 character, fixed-format string with all blanks replaced with [^], and with a decimal point as the 4th character. The only exception to this rule is that an entirely blank ICD-10 item must be submitted as a single [^].</p> <p>For example:</p> <ul style="list-style-type: none">-The ICD-10 code "A12." would be submitted as [A12.^^^].-The ICD-10 code "A12.3" would be submitted as [A12.3^^].-The ICD-10 code "A12.34" would be submitted as [A12.34^^].-The ICD-10 code "A12.345" would be submitted as [A12.345^]-The ICD-10 code "A12.3456" would be submitted as [A12.3456]-An entirely blank ICD-10 code would be submitted as [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG2_SEVERITY

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 2: severity rating	Asmt		Code	2	1387-1388

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
00		Asymptomatic, no treatment needed at this time
01		Symptoms well controlled with current therapy
02		Symptoms controlled with difficulty, affecting daily functioning; patient needs ongoing monitoring
03		Symptoms poorly controlled: patient needs frequent adjustment in treatment and dose monitoring
04		Symptoms poorly controlled: history of re-hospitalizations
^		No severity rating

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].
-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON =[01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG3_ICD

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 3: ICD code	Asmt		ICD	8	1389-1396

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
ICD-10		ICD-10 diagnosis code
^		Blank (no diagnosis code)

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-4885	Format	Fatal	FORMATTING OF ICD-10 DIAGNOSIS CODES ICD-10 diagnosis codes must conform with the following formatting rules: a) Character 1 must be alphabetic [A-Z,a-z]. b) Character 2 must be numeric [0-9]. c) Character 3 must be numeric [0-9] or alphabetic [A-Z,a-z]. d) Character 4 must be a decimal point. e) Characters 5 through 8 must be numeric [0-9], alphabetic [A-Z,a-z], or caret [^]. f) If any character 5 through 8 is equal to [^], all subsequent characters must equal [^]. Note that additional formatting rules for particular items may further restrict the range of allowable values in character 1. Also note that an entirely blank ICD code must be submitted as a single caret: [^].
-5001	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if a value submitted in items M1021_PRIMARY_DIAG_ICD, M1023_OTH_DIAG1_ICD, M1023_OTH_DIAG2_ICD, M1023_OTH_DIAG3_ICD, M1023_OTH_DIAG4_ICD, or M1023_OTH_DIAG5_ICD is not equal to [^], it must not equal (must not duplicate) any value submitted in the remaining items in this list.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON = [01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Supplemental Information

Info ID	Type	Text
-9110	Information	<p>If state law prohibits transmission of certain ICD codes (e.g., HIV or STD diagnoses), these codes will be removed by iQIES if found on records submitted by HHAs within that state. If any item within an ICD list contains such a code on a submitted record, it will be removed from the list. If any of these items is removed, but a valid code remains in a subsequent item on the list, the subsequent codes will be "moved up" so that no missing codes remain.</p> <p>Therefore, if a non-blank value is required in an ICD code list and all of the submitted items in that list contain blank and/or prohibited codes, a fatal error will result and the record will be rejected. As long as at least one item in such a list contains a non-blank, correctly-formatted, allowable code, a fatal error will not occur.</p>
-9150	Information	<p>If an ICD list contains multiple codes, there should be no intervening items in the list which are equal to [^]. For example, if a 5-item list is populated with 3 ICD codes, those codes should occupy items 1, 2, and 3; items 4 and 5 should be equal to [^].</p> <p>If the system finds a list which contains intervening items which are equal to [^], the values that are later in the list will be moved up to eliminate the intervening blank [^] item values. Diagnoses are only moved up within the same type of</p>
-9170	Information	<p>SUBMITTING ICD-10 DIAGNOSIS CODES</p> <p>If the ICD-10 item is active, it must be submitted as an 8 character, fixed-format string with all blanks replaced with [^], and with a decimal point as the 4th character. The only exception to this rule is that an entirely blank ICD-10 item must be submitted as a single [^].</p> <p>For example:</p> <ul style="list-style-type: none">-The ICD-10 code "A12." would be submitted as [A12.^^^].-The ICD-10 code "A12.3" would be submitted as [A12.3^^].-The ICD-10 code "A12.34" would be submitted as [A12.34^^].-The ICD-10 code "A12.345" would be submitted as [A12.345^].-The ICD-10 code "A12.3456" would be submitted as [A12.3456].-An entirely blank ICD-10 code would be submitted as [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG3_SEVERITY

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 3: severity rating	Asmt		Code	2	1397-1398

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
00		Asymptomatic, no treatment needed at this time
01		Symptoms well controlled with current therapy
02		Symptoms controlled with difficulty, affecting daily functioning; patient needs ongoing monitoring
03		Symptoms poorly controlled: patient needs frequent adjustment in treatment and dose monitoring
04		Symptoms poorly controlled: history of re-hospitalizations
^		No severity rating

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].
-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON =[01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG4_ICD

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 4: ICD code	Asmt		ICD	8	1399-1406

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
ICD-10		ICD-10 diagnosis code
^		Blank (no diagnosis code)

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-4885	Format	Fatal	FORMATTING OF ICD-10 DIAGNOSIS CODES ICD-10 diagnosis codes must conform with the following formatting rules: a) Character 1 must be alphabetic [A-Z,a-z]. b) Character 2 must be numeric [0-9]. c) Character 3 must be numeric [0-9] or alphabetic [A-Z,a-z]. d) Character 4 must be a decimal point. e) Characters 5 through 8 must be numeric [0-9], alphabetic [A-Z,a-z], or caret [^]. f) If any character 5 through 8 is equal to [^], all subsequent characters must equal [^]. Note that additional formatting rules for particular items may further restrict the range of allowable values in character 1. Also note that an entirely blank ICD code must be submitted as a single caret: [^].
-5001	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if a value submitted in items M1021_PRIMARY_DIAG_ICD, M1023_OTH_DIAG1_ICD, M1023_OTH_DIAG2_ICD, M1023_OTH_DIAG3_ICD, M1023_OTH_DIAG4_ICD, or M1023_OTH_DIAG5_ICD is not equal to [^], it must not equal (must not duplicate) any value submitted in the remaining items in this list.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON = [01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Supplemental Information

Info ID	Type	Text
-9110	Information	<p>If state law prohibits transmission of certain ICD codes (e.g., HIV or STD diagnoses), these codes will be removed by iQIES if found on records submitted by HHAs within that state. If any item within an ICD list contains such a code on a submitted record, it will be removed from the list. If any of these items is removed, but a valid code remains in a subsequent item on the list, the subsequent codes will be "moved up" so that no missing codes remain.</p> <p>Therefore, if a non-blank value is required in an ICD code list and all of the submitted items in that list contain blank and/or prohibited codes, a fatal error will result and the record will be rejected. As long as at least one item in such a list contains a non-blank, correctly-formatted, allowable code, a fatal error will not occur.</p>
-9150	Information	<p>If an ICD list contains multiple codes, there should be no intervening items in the list which are equal to [^]. For example, if a 5-item list is populated with 3 ICD codes, those codes should occupy items 1, 2, and 3; items 4 and 5 should be equal to [^].</p> <p>If the system finds a list which contains intervening items which are equal to [^], the values that are later in the list will be moved up to eliminate the intervening blank [^] item values. Diagnoses are only moved up within the same type of</p>
-9170	Information	<p>SUBMITTING ICD-10 DIAGNOSIS CODES</p> <p>If the ICD-10 item is active, it must be submitted as an 8 character, fixed-format string with all blanks replaced with [^], and with a decimal point as the 4th character. The only exception to this rule is that an entirely blank ICD-10 item must be submitted as a single [^].</p> <p>For example:</p> <ul style="list-style-type: none">-The ICD-10 code "A12." would be submitted as [A12.^^^].-The ICD-10 code "A12.3" would be submitted as [A12.3^^].-The ICD-10 code "A12.34" would be submitted as [A12.34^^].-The ICD-10 code "A12.345" would be submitted as [A12.345^].-The ICD-10 code "A12.3456" would be submitted as [A12.3456].-An entirely blank ICD-10 code would be submitted as [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG4_SEVERITY

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 4: severity rating	Asmt		Code	2	1407-1408

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
00		Asymptomatic, no treatment needed at this time
01		Symptoms well controlled with current therapy
02		Symptoms controlled with difficulty, affecting daily functioning; patient needs ongoing monitoring
03		Symptoms poorly controlled: patient needs frequent adjustment in treatment and dose monitoring
04		Symptoms poorly controlled: history of re-hospitalizations
^		No severity rating

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].
-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON = [01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG5_ICD

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 5: ICD code	Asmt		ICD	8	1409-1416

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
ICD-10		ICD-10 diagnosis code
^		Blank (no diagnosis code)

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-4885	Format	Fatal	FORMATTING OF ICD-10 DIAGNOSIS CODES ICD-10 diagnosis codes must conform with the following formatting rules: a) Character 1 must be alphabetic [A-Z,a-z]. b) Character 2 must be numeric [0-9]. c) Character 3 must be numeric [0-9] or alphabetic [A-Z,a-z]. d) Character 4 must be a decimal point. e) Characters 5 through 8 must be numeric [0-9], alphabetic [A-Z,a-z], or caret [^]. f) If any character 5 through 8 is equal to [^], all subsequent characters must equal [^]. Note that additional formatting rules for particular items may further restrict the range of allowable values in character 1. Also note that an entirely blank ICD code must be submitted as a single caret: [^].
-5001	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if a value submitted in items M1021_PRIMARY_DIAG_ICD, M1023_OTH_DIAG1_ICD, M1023_OTH_DIAG2_ICD, M1023_OTH_DIAG3_ICD, M1023_OTH_DIAG4_ICD, or M1023_OTH_DIAG5_ICD is not equal to [^], it must not equal (must not duplicate) any value submitted in the remaining items in this list.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON = [01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Supplemental Information

Info ID	Type	Text
-9110	Information	<p>If state law prohibits transmission of certain ICD codes (e.g., HIV or STD diagnoses), these codes will be removed by iQIES if found on records submitted by HHAs within that state. If any item within an ICD list contains such a code on a submitted record, it will be removed from the list. If any of these items is removed, but a valid code remains in a subsequent item on the list, the subsequent codes will be "moved up" so that no missing codes remain.</p> <p>Therefore, if a non-blank value is required in an ICD code list and all of the submitted items in that list contain blank and/or prohibited codes, a fatal error will result and the record will be rejected. As long as at least one item in such a list contains a non-blank, correctly-formatted, allowable code, a fatal error will not occur.</p>
-9150	Information	<p>If an ICD list contains multiple codes, there should be no intervening items in the list which are equal to [^]. For example, if a 5-item list is populated with 3 ICD codes, those codes should occupy items 1, 2, and 3; items 4 and 5 should be equal to [^].</p> <p>If the system finds a list which contains intervening items which are equal to [^], the values that are later in the list will be moved up to eliminate the intervening blank [^] item values. Diagnoses are only moved up within the same type of</p>
-9170	Information	<p>SUBMITTING ICD-10 DIAGNOSIS CODES</p> <p>If the ICD-10 item is active, it must be submitted as an 8 character, fixed-format string with all blanks replaced with [^], and with a decimal point as the 4th character. The only exception to this rule is that an entirely blank ICD-10 item must be submitted as a single [^].</p> <p>For example:</p> <ul style="list-style-type: none">-The ICD-10 code "A12." would be submitted as [A12.^^^].-The ICD-10 code "A12.3" would be submitted as [A12.3^^].-The ICD-10 code "A12.34" would be submitted as [A12.34^^].-The ICD-10 code "A12.345" would be submitted as [A12.345^]-The ICD-10 code "A12.3456" would be submitted as [A12.3456]-An entirely blank ICD-10 code would be submitted as [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)

Detailed Data Specifications Report

Section: I

Item ID: M1023_OTH_DIAG5_SEVERITY

Item Label	Item Group	LOINC Code	Item Type	Max Length	Fixed Format Start-End Bytes
Other diagnosis 5: severity rating	Asmt		Code	2	1417-1418

Item Subsets

Active: 01,03
Inactive: 04,05,06,07,08,09,XX

Item Values

Value	LOINC Code	Value Text
00		Asymptomatic, no treatment needed at this time
01		Symptoms well controlled with current therapy
02		Symptoms controlled with difficulty, affecting daily functioning; patient needs ongoing monitoring
03		Symptoms poorly controlled: patient needs frequent adjustment in treatment and dose monitoring
04		Symptoms poorly controlled: history of re-hospitalizations
^		No severity rating

Item Edits

Edit ID	Edit Type	Severity	Edit Text
-3060	Format	Fatal	VALUES OF CODE AND CHECKLIST ITEMS Only the coded values listed in the "Item Values" table of the Detailed Data Specifications Report may be submitted for this item.
-5201	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if character 1 of the Primary/Other ICD code in Column 2 is equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must equal [^].
-5211	Consistency	Fatal	If M0100_ASSMT_REASON=[01,03] and if the Primary/Other ICD code in Column 2 is NOT equal to [^] AND character 1 of the ICD code is NOT equal to [V,W,X,Y,Z,v,w,x,y,z], then the corresponding severity code must not equal [^].
-5221	Consistency	Fatal	If M0100_ASSMT_REASON =[01,03], and if the Primary/Other ICD code in Column 2 is equal to [^], then the corresponding severity code must equal [^].

Data Submission Specifications for the OASIS Item Set (V3.01.1)
Detailed Data Specifications Report
Section: I

Changes for Version

Type	ID	Description
Format	-3060	[V3.01.0]-Removed mappings to the goal items for GG0130 and GG0170, M0110_EPISODE_TIMING and M2200_THER_NEED_NA, since those items were deleted. Added mapping to new item O0350.